

25 TON FIXED HEIGHT TRIPOD JACK 7225A

The Model 7225A Fixed Height Tripod Jack is a 25 ton capacity, single stage hydraulic jack designed primarily for use in aircraft maintenance. It consists of a tripod structure, hydraulic cylinder/reservoir assembly, adjustable hand pump and swivel casters. The jack leg pads are raised off the ground by spring loaded casters. The casters will retract and the pads rest on the ground when a load is applied to the jack.

- MANUAL HAND PUMP WITH ADJUSTABLE PRESSURE SETTINGS
- CORROSION-RESISTANT DESIGN
- DURABLE CONSTRUCTION WITH HEAVY DUTY CASTERS

TYPICAL AIRCRAFT APPLICATIONS

Foward Fuselage	Wing	Mid Wing
BAC1-11	BAC1-11, GI, GII, GIII, GIV, GV, GVI, GVII, SF340	BAC1-11

THE MALABAR ADVANTAGE

Malabar Equipment is built to withstand harsh environmental conditions, rugged use and provide many years of continuous service. Our customers are guaranteed a quality product with each purchase and are assured of our continued product support whenever and wherever the need arises.

Tronair.com

sales@tronair.com • 1.800.426.6301 • 1 Air Cargo Parkway East, Swanton, Ohio 43558

STANDARD FEATURES

- Manual hand pump with high, medium and low pressure operating positions
- · Heavy duty swivel casters
- Rain hat (covers jack upper head)
- Hard chrome plated cylinder bore
- All unpainted parts are plated to resist corrosion
- Skydrol resistant paint (safety yellow)
- Factory proof load @ 150% of rated capacity
- · Shipping skid
- 3 year standard warranty
- · Shipment on domestic skid

OPTIONAL FEATURES

- AP: Air Operated Hydraulic Pump
- · GA: Load Gauge
- TH: Tow Handle

JACK ACCESSORIES

714APK: Repair Kit

25 TON FIXED HEIGHT TRIPOD JACK

	MODEL	7225A
	Rated Capacity	25 tons (22.7 m. tons)
	Side Load	15% of vertical load
	Roll Under Height	43 inches (1092 mm)
	Low Height	42 inches (1067 mm)
(0	Hydraulic Lift	32 inches (813 mm)
SPECIFICATIONS	Extension Screw	10 inches (254 mm)
CATI	Total Extended Height	84 inches (2134 mm)
E S	Oil Pressure at Rated Capacity	3500 psig (246 kg/sq cm)
3PE(Safety Pop-off Valve set at	27.5 tons (24.9 m. tons)
0,	Proof Load	37.5 tons (34.0 m. tons)
	Reservoir Capacity	2.2 gallons (8.3 liters)
	Hydraulic Fluid	MIL-PRF-5606 or equivalent
	Maximum Towing Speed	5 mph (8 km/h)
	Approximate Jack Net Weight	575 lbs (261 kg)

AVAILABLE PART NUMBERS

(Specify with order)

722500A-4 AP, GA, TH

PACKING CODES & OPTIONS

(Specify with order)

Domestic Skid - Jack Set-up

KD: Domestic Skid – Jack Knocked Down (Additional Cost)

EC: Export Crate - Jack Set-up (Additional Cost)

ECKD: Export Crate – Jack Knocked Down (Additional Cost)

Tronair.com

sales@tronair.com 1.800.426.6301 1 Air Cargo Parkway East Swanton, Ohio 43558

SOLD & SERVICED BY:





















